

SOT-23 Plastic-Encapsulate Transistors

BCW61 TRANSISTOR (PNP)

FEATURES

- Low current
- Low voltage
- General Purpose Transistor

MARKING:

BCW61A: BA

BCW61B: BB


BCW61C: BC

BCW61D: BD

MAXIMUM RATINGS ($T_a=25^{\circ}\text{C}$ unless otherwise noted)

Symbol	Parameter	Value	Unit
V_{CBO}	Collector-Base Voltage	-32	V
V_{CEO}	Collector-Emitter Voltage	-32	V
V_{EBO}	Emitter-Base Voltage	-5	V
I_C	Collector Current	-100	mA
P_C	Collector Power Dissipation	250	mW
$R_{\theta JA}$	Thermal Resistance From Junction To Ambient	500	$^{\circ}\text{C}/\text{W}$
T_J, T_{stg}	Operation Junction and Storage Temperature Range	-55~+150	$^{\circ}\text{C}$

SOT - 23



1. BASE


2. EMITTER

3. COLLECTOR

ELECTRICAL CHARACTERISTICS (T_a=25°C unless otherwise specified)

Parameter	Symbol	Test conditions		Min	Typ	Max	Unit
Collector-base breakdown voltage	V _{(BR)CBO}	I _C =-10μA, I _E =0		-32			V
Collector-emitter breakdown voltage	V _{(BR)CEO}	I _C =-1mA, I _B =0		-32			V
Emitter-base breakdown voltage	V _{(BR)EBO}	I _E =-10μA, I _C =0		-5			V
Collector cut-off current	I _{CBO}	V _{CB} =-32V, I _E =0				-0.02	μA
Emitter cut-off current	I _{EBO}	V _{EB} =-4V, I _C =0				-0.02	μA
DC current gain	h _{FE(1)}	V _{CE} =-5V, I _C =-10μA	BCW61B	30			
			BCW61C	40			
			BCW61D	100			
	h _{FE(2)}	V _{CE} =-5V, I _C =-2mA	BCW61A	120		220	
			BCW61B	180		310	
			BCW61C	250		460	
			BCW61D	380		630	
	h _{FE(3)}	V _{CE} =-1V, I _C =-50mA	BCW61A	60			
			BCW61B	80			
			BCW61C	100			
			BCW61D	110			
Collector-emitter saturation voltage	V _{CE(sat)}	I _C =-10mA, I _B =-0.25mA		-60		-250	mV
		I _C =-50mA, I _B =-1.25mA		-120		-550	mV
Base-emitter saturation voltage	V _{BE(sat)}	I _C =-10mA, I _B =-0.25mA		-0.6		-0.85	V
		I _C =-50mA, I _B =-1.25mA		-0.68		-1.05	V
Base-emitter voltage	V _{BE}	V _{CE} =-5V, I _C =-2mA		-0.6		-0.75	V
Transition frequency	f _T	V _{CE} =-5V, I _C =-10mA, f=100MHz		100			MHz
Collector output capacitance	C _{ob}	V _{CB} =-10V, I _E =0, f=1MHz			4.5		pF
Emitter input capacitance	C _{ib}	V _{EB} =-0.5V, I _C =0, f=1MHz			11		pF

SOT-23 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP		0.037 TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

SOT-23 Suggested Pad Layout



Note:

1. Controlling dimension: in millimeters.
2. General tolerance: $\pm 0.05\text{mm}$.
3. The pad layout is for reference purposes only.

NOTICE

JSCJ reserves the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. JSCJ does not assume any liability arising out of the application or use of any product described herein.

SOT-23 Embossed Carrier Tape



Packaging Description:


SOT-23 parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 3,000 units per 7" or 17.8cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
SOT-23	3.15	2.77	1.22	Ø1.50	1.75	3.50	4.00	4.00	2.00	8.00

SOT-23 Tape Leader and Trailer



SOT-23 Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
7"Dia	Ø178.00	54.40	13.00	R78.00	R25.60	R6.50	9.50	12.30

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
3000 pcs	7 inch	45,000 pcs	203×203×195	180,000 pcs	438×438×220	