

TO-92K Plastic-Encapsulate Thyristors

CT401G 4Q TRIACs

MAIN CHARACTERISTICS


$I_{T(RMS)}$		1A
V_{DRM}/V_{RRM}	CT401G-600T/S	600V
	CT401G-800T/S	800V
V_{TM}		1.55V

FEATURES

- NPNPN 5-layer Structure TRIACs
- Mesa Glass Passivated Technology
- Multi Layers Metal Electrodes
- High Junction Temperature
- Good Commutation Performance

APPLICATIONS

- Heater Control
- Motor Speed Controller
- Mixer



MARKING



CT401G:Series Code
600S:Depends on V_{DRM}
and I_{GT}
XXX:Internal Code

ABSOLUTE RATINGS ($T_a=25^{\circ}\text{C}$ unless otherwise noted)

Symbol	Parameter	Test condition		Value	Unit
V_{DRM}/V_{RRM}	Repetitive peak off-state voltage	$T_j=25^{\circ}\text{C}$	CT401G-600T/S	600	V
			CT401G-800T/S	800	V
$I_{T(RMS)}$	RMS on-state current	TO- 92K($T_c \leq 51^{\circ}\text{C}$), Fig. 1,2		1	A
I_{TSM}	Non repetitive surge peak on-state current	Full sine wave , $T_j(\text{init})=25^{\circ}\text{C}$, $t_p=20\text{ms}$; Fig. 3,5		10	A
I^2t	I^2t value	$t_p=10\text{ms}$		1.28	A^2s
di_T/dt	Critical rate of rise of on-state current	$I_G=2 \cdot I_{GT}$, $t_r \leq 10\text{ns}$, $F=120\text{Hz}$, $T_j=125^{\circ}\text{C}$	I - II -III	50	$\text{A}/\mu\text{s}$
			IV	10	
I_{GM}	Peak gate current	$t_p=20\mu\text{s}$, $T_j=125^{\circ}\text{C}$		2	A
$P_{G(AV)}$	Average gate power	$T_j=125^{\circ}\text{C}$		0.5	W
T_{STG}	Storage temperature			-40~+150	$^{\circ}\text{C}$
T_j	Operating junction temperature			-40~+125	


ELECTRICAL CHARACTERISTICS (T_a=25°C unless otherwise specified)

Symbol	Parameter	Test condition		Value		Unit
				T	S	
I _{GT}	Gate trigger current	V _D =12V, I _T =0.1A, T _J =25°C, Fig. 6	I - II -III	≤3	≤8	mA
			IV	≤5	≤10	
V _{GT}	Gate trigger voltage		I - II -III - IV	≤1.3		V
V _{GD}	Non-triggering gate voltage	VD=VDRM, T _J =125°C		≥0.2		V
I _H	Holding current	V _D =12V, I _{GT} =0.1A, T _J =25°C, Fig. 6	I - II -III - IV	≤5	≤5	mA
I _L	Latching current		I -III- IV	≤6	≤10	mA
			II	≤10	≤15	mA
dV _D /dt	Critical rate of rise of off-state	V _D =67%V _{DRM} , Gate Open T _J =125°C		≥20	≥50	V/μs
V _{TM}	On-state Voltage	I _{TM} =1.5A ,tp=380μs , Fig. 4		≤1.55		V
I _{DRM} / I _{RRM}	Repetitive peak off-state current	V _D =V _{DRM} /V _{RRM} , T _J =25°C		≤5	≤5	μA
		V _D =V _{DRM} /V _{RRM} ,T _J =125°C		≤0.1	≤0.1	mA

THERMAL RESISTANCES

Symbol	Parameter	Value	Unit
R _{th} (j-c)	Junction to case (AC)	TO-92K	60 °C/W
R _{th} (j-a)	Junction to ambient	TO-92K	150 °C/W

PART NUMBER



CHARACTERISTICS CURVES

FIG.1: Maximum power dissipation versus RMS on-state current (full cycle)




FIG.2: RMS on-state current versus case temperature (full cycle)




FIG.3: Surge peak on-state current versus number of cycles




FIG.4: On-state characteristics (maximum values)




FIG.5: Non-repetitive surge peak on-state current for a sinusoidal pulse with width $t_p < 10ms$






FIG.6: Relative variations of gate trigger current, holding current and latching current versus junction temperature (typical values)



TO-92K PACKAGE OUTLINE DIMENSIONS



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	4.45		5.20	0.175		0.205
B	4.32		5.33	0.170		0.210
C	3.18		4.19	0.125		0.165
D	0.407		0.533	0.016		0.021
E	0.60		0.80	0.024		0.031
F	-	1.1	-	-	0.043	-
G	-	1.27	-	-	0.050	-
H	-	2.30	-	-	0.091	-
J	0.36		0.50	0.014		0.020
K	12.70		15.0	0.500		0.591
N	2.04		2.66	0.080		0.105
P	1.86		2.06	0.073		0.081
V	-		4.3	-		0.169

NOTICE

JSCJ reserves the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. JSCJ does not assume any liability arising out of the application or use of any product described herein.