



**TO-92L Plastic-Encapsulate Transistors****KTC3206** TRANSISTOR (NPN)**FEATURE**


- High Breakdown Voltage : $V_{CEO}=150V(\text{Min.})$
- Low Output Capacitance : $C_{ob}=5.0pF(\text{Max.})$
- High Transition Frequency : $f_T=120MHz(\text{Typ.})$.

TO-92L

1. EMITTER
2. COLLECTOR
3. BASE

**MARKING**

C3206=Device code
Solid dot= Green molding compound device,
if none, the normal device
XXX=Code

Equivalent Circuit**ORDERING INFORMATION**

Part Number	Package	Packing Method	Pack Quantity
KTC3206	TO-92L	Bulk	500pcs/Bag
KTC3206-TA	TO-92L	Tape	2000pcs/Box

MAXIMUM RATINGS ($T_a=25^{\circ}\text{C}$ unless otherwise noted)

Symbol	Parameter	Value	Unit
V_{CBO}	Collector-Base Voltage	200	V
V_{CEO}	Collector-Emitter Voltage	150	V
V_{EBO}	Emitter-Base Voltage	5	V
I_C	Collector Current -Continuous	50	mA
P_C	Collector Power Dissipation	1	W
T_J, T_{stg}	Operation Junction and Storage Temperature Range	-55-150	$^{\circ}\text{C}$

ELECTRICAL CHARACTERISTICS


$T_a=25^{\circ}\text{C}$ unless otherwise specified

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	$V(\text{BR})_{\text{CBO}}$	$I_{\text{C}}=100\mu\text{A}$, $I_{\text{E}}=0$	200			V
Collector-emitter breakdown voltage	$V(\text{BR})_{\text{CEO}}$	$I_{\text{C}}=1\text{mA}$, $I_{\text{B}}=0$	150			V
Emitter-base breakdown voltage	$V(\text{BR})_{\text{EBO}}$	$I_{\text{E}}=100\mu\text{A}$, $I_{\text{C}}=0$	5			V
Collector cut-off current	I_{CBO}	$V_{\text{CB}}=200\text{V}$, $I_{\text{E}}=0$			0.1	μA
Emitter cut-off current	I_{EBO}	$V_{\text{EB}}=5\text{V}$, $I_{\text{C}}=0$			0.1	μA
DC current gain	h_{FE}	$V_{\text{CE}}=5\text{V}$, $I_{\text{C}}=10\text{mA}$	70		240	
Collector-emitter saturation voltage	$V_{\text{CE(sat)}}$	$I_{\text{C}}=10\text{mA}$, $I_{\text{B}}=1\text{mA}$			0.5	V
Base-emitter voltage	$V_{\text{BE(sat)}}$	$I_{\text{C}}=10\text{mA}$, $I_{\text{B}}=1\text{mA}$			1	V
Transition frequency	f_{T}	$V_{\text{CE}}=30\text{V}$, $I_{\text{C}}=10\text{mA}$		120		MHz
Collector Output Capacitance	C_{ob}	$V_{\text{CB}}=10\text{V}$, $I_{\text{E}}=0$, $f=1\text{MHz}$			5.0	pF

CLASSIFICATION OF h_{FE}


Rank	O	Y
Range	70-140	120-240

TO-92L Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	3.750	4.050	0.148	0.159
A1	1.280	1.580	0.050	0.062
b	0.380	0.550	0.015	0.022
b1	0.620	0.780	0.024	0.031
c	0.350	0.450	0.014	0.018
D	4.750	5.050	0.187	0.199
D1	4.000		0.157	
E	7.850	8.150	0.309	0.321
e	1.270 TYP.		0.050 TYP.	
e1	2.440	2.640	0.096	0.104
L	13.800	14.200	0.543	0.559
Φ		1.600		0.063
h	0.000	0.300	0.000	0.012

TO-92L Suggested Pad Layout




Note:

1. Controlling dimension: in millimeters.
2. General tolerance: ± 0.05 mm.
3. The pad layout is for reference purposes only.

NOTICE


JSCJ reserves the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. JSCJ does not assume any liability arising out of the application or use of any product described herein.

TO-92L PACKAGE TAPING DIMENSION



Dimensions are in millimeter

A1	A	T	P	P0	P2	F1	F2	W
4.9	8.0	3.9	12.7	12.7	6.35	2.5	2.5	18.0
W0	W1	W2	H	H0	D0	t1	t2	ΔP
6.0	9.0	1.0	19.0	16.0	4.0	0.4	0.2	0



Package	Box	Box Size(mm)	Carton	Carton Size(mm)
TO-92L	2000 pcs	333×203×42	20,000 pcs	493×400×264