

## Cautions and Warnings

Please be noted that this spec is only for reference if you have projects designed with the product number listed in. If you are looking for new project design-in, please find BBUP Series specification/datasheet on Chilisin website. Or you may find our sales contact for more information on old part number at your convenience. Appreciated your attention and understanding.


**Note:** Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

## Multilayer Ferrite Chip Beads




Chilisin offers a wide range of multi-layered ferrite chip beads with various sizes, frequency characteristics, and impedance values for EMI solutions. These ferrite formulas are used to compose seven types of EMI suppression chip beads: SB, GB, PB, UPB, NB, HF, and VPB series.

### Product Identification



- Product symbol: SB, GB, PB, UPB, NB, HF, VPB
- Packaging: T : Tape and Reel ; B : Bulk
- Tolerance: Y =  $\pm 25\%$ ; M =  $\pm 20\%$ ; T:  $\pm 30\%$
- Note: RoHS Compliant

### Shape and Dimensions



Dimensions in mm


| TYPE    | A              | B               | C              | D               |
|---------|----------------|-----------------|----------------|-----------------|
| ①060303 | 0.6 $\pm$ 0.03 | 0.30 $\pm$ 0.03 | 0.3 $\pm$ 0.03 | 0.15 $\pm$ 0.05 |
| ②100505 | 1.0 $\pm$ 0.10 | 0.50 $\pm$ 0.10 | 0.5 $\pm$ 0.10 | 0.25 $\pm$ 0.10 |
| ③160805 | 1.6 $\pm$ 0.15 | 0.80 $\pm$ 0.15 | 0.5 $\pm$ 0.15 | 0.3 $\pm$ 0.2   |
| ④160808 | 1.6 $\pm$ 0.15 | 0.80 $\pm$ 0.15 | 0.8 $\pm$ 0.15 | 0.3 $\pm$ 0.2   |
| ⑤201209 | 2.0 $\pm$ 0.20 | 1.25 $\pm$ 0.20 | 0.9 $\pm$ 0.20 | 0.5 $\pm$ 0.3   |
| ⑥321611 | 3.2 $\pm$ 0.20 | 1.60 $\pm$ 0.20 | 1.1 $\pm$ 0.20 | 0.5 $\pm$ 0.3   |
| ⑦453215 | 4.5 $\pm$ 0.25 | 3.20 $\pm$ 0.20 | 1.5 $\pm$ 0.20 | 0.5 $\pm$ 0.3   |

- ① : SBY / SBJ / NB / PB    ② : SBY / SBJ / NB / PB / UPB / HF  
 ③ : UPB    ④ : SBK / SBJ / GB / PB / NB / UPB / VPB  
 ⑤ : SBK / GB / PB / UPB    ⑥ : SBY / SBK / PBY / UPB  
 ⑦ : PB / UPB

### Dimension Conversion

| Code   | Dimension in mm<br>(AxBxC) | EIA  |
|--------|----------------------------|------|
| 060303 | 0.6X0.3X0.3                | 0201 |
| 100505 | 1.0X0.5X0.5                | 0402 |
| 160805 | 1.6x0.8x0.5                | 0603 |
| 160808 | 1.6x0.8x0.8                | 0603 |
| 201209 | 2.0x1.2x0.9                | 0805 |
| 321611 | 3.2x1.6x1.1                | 1206 |
| 453215 | 4.5x3.2x1.5                | 1812 |

### Recommended Pattern



Dimensions in mm

| TYPE    | A         | B           | C         |
|---------|-----------|-------------|-----------|
| ①060303 | 0.2 ~ 0.3 | 0.75 ~ 1.05 | 0.3       |
| ②100505 | 0.4       | 1.2 ~ 1.4   | 0.5       |
| ③160805 | 0.7 ~ 0.8 | 1.8 ~ 2.0   | 0.6 ~ 0.8 |
| ④160808 | 0.7 ~ 0.8 | 1.8 ~ 2.0   | 0.6 ~ 0.8 |
| ⑤201209 | 1.0 ~ 1.2 | 2.6 ~ 4.0   | 1.0 ~ 1.2 |
| ⑥321611 | 2.0       | 4.2 ~ 5.2   | 1.2       |
| ⑦453215 | 3.0       | 5.5 ~ 6.5   | 2.4       |

- \* Don't apply narrower pattern than listed above to PBY and UPB. Narrow pattern might cause excessive heat or open circuit.

# SMD Multilayer Ferrite Chip Beads – UPB Series









## Electrical Characteristics

| Part Number       | Impedance<br>( $\Omega \pm 25\%$ ) | Test Frequency<br>(MHz) | RDC<br>( $\Omega$ ) Max | Rated current<br>(mA) Max |
|-------------------|------------------------------------|-------------------------|-------------------------|---------------------------|
| UPB100505T-330Y-N | 33                                 | 100                     | 0.022                   | 3000                      |
| UPB100505T-600Y-N | 60                                 | 100                     | 0.032                   | 2500                      |
| UPB100505T-800Y-N | 80                                 | 100                     | 0.038                   | 2300                      |
| UPB100505T-121Y-N | 120                                | 100                     | 0.055                   | 2000                      |
| UPB100505T-181Y-N | 180                                | 100                     | 0.090                   | 1500                      |
| UPB100505T-221Y-N | 220                                | 100                     | 0.100                   | 1400                      |
| UPB100505T-331Y-N | 330                                | 100                     | 0.150                   | 1200                      |
| UPB100505T-471Y-N | 470                                | 100                     | 0.200                   | 1000                      |

**Note:** When ordering, please specify tolerance code. Tolerance : Y $\pm 25\%$

- Operating temperature range - 55°C ~ 125°C(Including self - temperature rise)
- Rate Current : Applied the current to coils, the temperature rise shall not be more than 30°C
- Measure Equipment :  
Z : HP4291A  
RDC : HP4338B or CHEN HWA 502

## Test Instruments : Agilent E4991A Impedance / Material Analyzer



## SMD Multilayer Ferrite Chip Beads – UPB Series








### Electrical Characteristics

| Part Number       | Impedance<br>( $\Omega \pm 25\%$ ) | Test Frequency<br>(MHz) | RDC<br>( $\Omega$ ) Max | Rated current<br>(mA) Max |
|-------------------|------------------------------------|-------------------------|-------------------------|---------------------------|
| UPB160805T-260Y-N | 26                                 | 100                     | 0.007                   | 6000                      |
| UPB160805T-300Y-N | 30                                 | 100                     | 0.007                   | 6000                      |
| UPB160805T-700Y-N | 70                                 | 100                     | 0.020                   | 4000                      |
| UPB160805T-101Y-N | 100                                | 100                     | 0.025                   | 3000                      |
| UPB160805T-121Y-N | 120                                | 100                     | 0.025                   | 3000                      |
| UPB160805T-221Y-N | 220                                | 100                     | 0.040                   | 2500                      |
| UPB160805T-331Y-N | 330                                | 100                     | 0.070                   | 1500                      |

**Note:** When ordering, please specify tolerance code. Tolerance : Y= $\pm 25\%$

- Operating temperature range - 55°C ~ 125°C(Including self - temperature rise)
- Rate Current : Applied the current to coils, the temperature rise shall not be more than 30°C
- Measure Equipment :  
Z : HP4291A  
RDC : HP4338B or CHEN HWA 502

### Test Instruments : Agilent E4991A Impedance / Material Analyzer



# SMD Multilayer Ferrite Chip Beads – UPB Series








## Electrical Characteristics

| Part Number       | Impedance<br>( $\Omega \pm 25\%$ ) | Test Frequency<br>(MHz) | RDC<br>( $\Omega$ ) Max | Rated current<br>(mA) Max |
|-------------------|------------------------------------|-------------------------|-------------------------|---------------------------|
| UPB160808T-100Y-N | 10                                 | 100                     | 0.010                   | 5000                      |
| UPB160808T-300Y-N | 30                                 | 100                     | 0.015                   | 4500                      |
| UPB160808T-600Y-N | 60                                 | 100                     | 0.020                   | 4000                      |
| UPB160808T-700Y-N | 70                                 | 100                     | 0.020                   | 4000                      |
| UPB160808T-101Y-N | 100                                | 100                     | 0.030                   | 3000                      |
| UPB160808T-121Y-N | 120                                | 100                     | 0.030                   | 3000                      |
| UPB160808T-181Y-N | 180                                | 100                     | 0.050                   | 2000                      |
| UPB160808T-221Y-N | 220                                | 100                     | 0.040                   | 2500                      |

**Note:** When ordering, please specify tolerance code. Tolerance : Y= $\pm 25\%$

- Operating temperature range - 55°C ~ 125°C(Including self - temperature rise)
- Rate Current : Applied the current to coils, the temperature rise shall not be more than 30°C
- Measure Equipment :  
Z : HP4291A  
RDC : HP4338B or CHEN HWA 502

## Test Instruments : Agilent E4991A Impedance / Material Analyzer



# SMD Multilayer Ferrite Chip Beads – UPB Series


## Electrical Characteristics

| Part Number       | Impedance ( $\Omega \pm 25\%$ ) | Test Frequency (MHz) | RDC ( $\Omega$ ) Max | Rated current (mA) Max |
|-------------------|---------------------------------|----------------------|----------------------|------------------------|
| UPB201209T-150Y-N | 15                              | 100                  | 0.012                | 6000                   |
| UPB201209T-220Y-N | 22                              | 100                  | 0.012                | 6000                   |
| UPB201209T-300Y-N | 30                              | 100                  | 0.012                | 6000                   |
| UPB201209T-500Y-N | 50                              | 100                  | 0.015                | 6000                   |
| UPB201209T-600Y-N | 60                              | 100                  | 0.018                | 6000                   |
| UPB201209T-800Y-N | 80                              | 100                  | 0.02                 | 6000                   |
| UPB201209T-101Y-N | 100                             | 100                  | 0.02                 | 5000                   |
| UPB201209T-121Y-N | 120                             | 100                  | 0.02                 | 5000                   |
| UPB201209T-201Y-N | 200                             | 100                  | 0.04                 | 3000                   |
| UPB201209T-221Y-N | 220                             | 100                  | 0.04                 | 3000                   |
| UPB201209T-301Y-N | 300                             | 100                  | 0.05                 | 3000                   |
| UPB201209T-331Y-N | 330                             | 100                  | 0.05                 | 3000                   |

**Note:** When ordering, please specify tolerance code. Tolerance : Y= $\pm 25\%$

- Operating temperature range - 55°C ~ 125°C(Including self - temperature rise)
- Rate Current : Applied the current to coils, the temperature rise shall not be more than 30°C
- Measure Equipment :  
Z : HP4291A  
RDC : HP4338B or CHEN HWA 502




**Test Instruments :** Agilent E4991A Impedance / Material Analyzer



Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

## SMD Multilayer Ferrite Chip Beads – UPB Series

Test Instruments : Agilent E4991A Impedance / Material Analyzer



# SMD Multilayer Ferrite Chip Beads – UPB Series









## Electrical Characteristics

| Part Number       | Impedance<br>( $\Omega \pm 25\%$ ) | Test Frequency<br>(MHz) | RDC<br>( $\Omega$ ) Max | Rated current<br>(mA) Max |
|-------------------|------------------------------------|-------------------------|-------------------------|---------------------------|
| UPB321611T-300Y-N | 30                                 | 100                     | 0.012                   | 6000                      |
| UPB321611T-600Y-N | 60                                 | 100                     | 0.012                   | 6000                      |
| UPB321611T-800Y-N | 80                                 | 100                     | 0.012                   | 6000                      |
| UPB321611T-101Y-N | 100                                | 100                     | 0.012                   | 6000                      |
| UPB321611T-121Y-N | 120                                | 100                     | 0.012                   | 6000                      |
| UPB321611T-151Y-N | 150                                | 100                     | 0.020                   | 4500                      |
| UPB321611T-181Y-N | 180                                | 100                     | 0.020                   | 4500                      |
| UPB321611T-221Y-N | 220                                | 100                     | 0.020                   | 4500                      |

**Note:** When ordering, please specify tolerance code. Tolerance : Y=±25%

- Operating temperature range - 55°C ~ 125°C(Including self - temperature rise)
- Rate Current : Applied the current to coils, the temperature rise shall not be more than 30°C
- Measure Equipment :  
Z : HP4291A  
RDC : HP4338B or CHEN HWA 502

**Test Instruments :** Agilent E4991A Impedance / Material Analyzer







## SMD Multilayer Ferrite Chip Beads – UPB Series

### Electrical Characteristics

| Part Number       | Test Frequency (MHz) | Impedance ( $\Omega \pm 25\%$ ) | DC Resistance ( $\Omega$ ) Max | Rated current (mA) Max |
|-------------------|----------------------|---------------------------------|--------------------------------|------------------------|
| UPB453215T-560Y-N | 100                  | 56                              | 0.010                          | 10000                  |
| UPB453215T-800Y-N | 100                  | 80                              | 0.010                          | 9000                   |
| UPB453215T-121Y-N | 100                  | 120                             | 0.020                          | 6000                   |
| UPB453215T-151Y-N | 100                  | 150                             | 0.020                          | 6000                   |

Test Instruments : Agilent E4991A Impedance / Material Analyzer





单击下面可查看定价，库存，交付和生命周期等信息

[>>CHILISIN\(奇力新\)](#)